

uniview

IPC222E-IR-F60(120) IPC222ER-F36 2MP Network IR Bullet Camera



Features :

- 1/2.8" progressive scan CMOS, 2MP
- ONVIF compliant
- IP66
- DC/PoE, $\pm 25\%$ wide voltage range
- Corridor mode

IPC222E-IR-F60(120) IPC222ER-F36

2MP Network IR Bullet Camera

Camera	IPC222ER-F36	IPC222E-IR-F60	IPC222E-IR-F120
Sensor	1/2.8", 2 megapixel, progressive scan, CMOS		
Shutter	Auto/manual, 1/6~1/8000s		
Lens	3.6mm@F1.8	6mm	12mm
Angle of View (H)	85°	53.2°	28°
Day/Night	IR-cut filter with auto switch (ICR)		
Min. Illumination	Color: 0.06lux (F1.6, 50IRE), black & white: 0.03lux (F1.6, 50IRE)		
S/N	>52dB		
Image Rotation	Supported		
Video			
Maximum Resolution	1920 × 1080		
Video Compression	H.264, MJPEG		
Frame Rate	1080P (1920*1080) 30fps; 720P (1280*720) 30fps; D1 (720*576) 25fps		
9:16 Corridor Mode	Supported		
ROI(Region of Interest)	Supported		
Video Streaming	Triple		
Audio			
Audio Compression	G.711		
Two-way Audio	Supported		
Network			
Protocols	L2TP, IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, Qos, NTP, FTP, HTTP, SNMP, SIP		
Compatible Integration	ONVIF, IMOS, API		
Interface			
Audio I/O	Audio cable Input: impedance 35 kΩ ; amplitude 2V [p-p] Output: impedance 600 Ω ; amplitude 2V [p-p]		
Alarm I/O	1/ 1		
Network	10M/100M Base-TX Ethernet		
General			
Power	12V DC, or PoE (IEEE802.3af) Power consumption: 3.5W (7.5W with IR on)		
Dimensions (L × W × H)	187.8 × 76 × 44 mm (7.4" × 3.0" × 1.7")		
Weight	0.58 kg (1.3 lb)		
Working Environment	-30°C ~ +60°C (-22°F ~ 140°F), humidity ≤ 90% RH(non-condensing)		
Ingress Protection	IP66		

*Product specifications and availability are subject to change without notice.

