

uniview

IPC2122SR3 Series 2MP Network IR Mini Bullet Camera



Features:

- 1/2.8" progressive scan CMOS
- Smart IR, up to 30m (98ft) IR distance
- DC12V, PoE, wide voltage range of $\pm 25\%$
- IP66

IPC2122SR3 Series

2MP Network IR Mini Bullet Camera

Camera	IPC2122SR3-PF36	IPC2122SR3-PF60	IPC2122SR3-PF120
Sensor	1/2.8", 2 megapixel, progressive scan, CMOS		
Lens	3.6mm@F1.8 Angle of view (H): 80.5°	6.0mm@F1.8 Angle of view (H): 49.9°	12.0mm@F1.8 Angle of view (H): 25.8°
Shutter	Auto/Manual, 1/6~1/8000s		
Min. Illumination	Color: 0.06lux (F1.4, 50IRE) 0lux with IR on		
Day/Night	IR-cut filter with auto switch (ICR)		
IR Range	Up to 30m (98ft) IR range		
S/N	>52dB		
WDR	Digital		
Noise Reduction	2D/3D		
Video			
Max. Resolution	1920×1080		
Video Compression	H.264/MJPEG		
Frame Rate	1080P (1920×1080): max. 30fps; 720P (1280×720): max. 30fps; D1 (720×576): max. 25fps		
Video Streaming	Triple		
9:16 Corridor Mode	Supported		
ROI	Supported		
Motion Detection	Up to 2 areas		
Network			
Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, DNS, DDNS, NTP, FTP, UPnP, HTTP		
Compatible Integration	ONVIF		
Interface			
Network	1 RJ45 10M/100M Base-TX Ethernet		
General			
Power	12V DC, or PoE (IEEE802.3 af), 2.0W (6.4W with IR on)		
Dimensions (L × W × H)	157.3 × 62.4 × 63mm (6.2" × 2.5" × 2.5")		
Weight	0.45kg (0.99lb)		
Working Environment	-35°C ~ +60°C (-31°F ~ 140°F), humidity ≤ 90% RH (non-condensing)		
Ingress Protection	IP66		

*Product specifications and availability are subject to change without notice.

